



| LENGTH | SKU             |
|--------|-----------------|
| 2 m    | NC-Core-A90-002 |
| 3 m    | NC-Core-A90-003 |

Space-saving 90° USB-C without performance loss.

Norrd CORE A90 is a full-spec professional USB-C cable built for installations where space is tight and reliability matters. With 90° angled connectors on both ends, CORE A90 does not bend or break as easy as conventional USB-C Cables. CORE A90 delivers uncompromised performance: USB data up to 20 Gbps, DisplayPort Alt Mode video and up to 100W Power Delivery charging. Each cable is e-marked and engineered for stable, high-bandwidth BYOD and pro-AV environments, making it the go-to solution when you need a neat install and the full capabilities of USB-C.

## KEY FEATURES

### Key Features

- 90° angled USB-C connectors on both ends for clean routing in tight spaces
- Full-feature USB-C with USB 3.2 Gen 2x2 data up to 20 Gbps
- Supports DisplayPort Alt Mode video up to 4K@60Hz (device dependent)
- Up to 100W Power Delivery for reliable BYOD laptop charging
- Pro-grade build with e-marked electronics and reinforced strain relief

| GENERAL                |                                 |
|------------------------|---------------------------------|
| Product Series         | NC-Core-A90 Series              |
| Product Name           | USB-C to USB-C Copper Cable     |
| Cable Type             | Passive copper                  |
| Available Lengths      | 2m, 3m                          |
| Connector Type         | USB Type-C Male to Male         |
| Connector Style        | Right-Angled to Right-Angled    |
| E-Marker               | HUSB332D                        |
| VIDEO                  |                                 |
| Video Support          | Yes                             |
| Max Resolution         | 4K@60Hz                         |
| DATA                   |                                 |
| USB 3.2 Gen 2x2        | 20Gbps                          |
| Backward Compatibility | USB 2.0 / 1.1                   |
| POWER                  |                                 |
| Power Delivery         | 100W Max                        |
| Voltage                | 20V                             |
| Current                | 5A                              |
| MECHANICAL             |                                 |
| Cable OD               | 5.2±0.2mm                       |
| Cable Color            | Black                           |
| Jacket Material        | TPE                             |
| Conductor Gauge Data   | 30 AWG                          |
| Conductor Gauge Power  | 21 AWG                          |
| Shielding              | Aluminum Foil + Mylar + Braided |
| PACKING                |                                 |
| Packaging Type         | Paper cable ties                |