

NORRD

Robust Install-cable HDMI 2.0



LENGTH	SKU
3 m	NC-H-INSTALL-003
5 m	NC-H-INSTALL-005
7,5 m	NC-H-INSTALL-0075

Rugged HDMI for permanent routing.

Installation-friendly HDMI cable for permanent routing in conduits or longer passive runs between devices. Larger diameter helps maintain HDMI 2.0 performance.Full tested in all lenghts togheter with Norrd Drop 3m i full 4K60.

KEY FEATURES

- Installation-grade HDMI 2.0 cable for permanent routing
- Supports 4K@60Hz and full 18 Gbps bandwidth
- Thicker, more robust construction for longer passive runs
- Form-stiff design makes conduit pulling easier
- Built for reliable pro AV installations

GENERAL	
Cable Type	Passive copper HDMI
Available Lengths	3m, 5m, 7.5m
Interface	HDMI-A Male to HDMI-A Male
VIDEO	
HDMI Standard	HDMI 2.0
HDCP	HDCP 2.2
Max Resolution	4K@60Hz
Bandwidth	18Gbps
Pixel Clock	6Gb/s per channel
Color Depth	16/24bit RGB/YUV
3D Support	Yes
EDID	Supported
CEC	Supported
HEAC	Supported
Audio Return Channel (ARC)	Supported
AUDIO	
Audio Transmission	Digital Audio
Multi-Stream Audio	Supported
MECHANICAL	
Cable OD	7.8±0.2mm
Cable Color	Black
Jacket Material	PVC
Connector Material	Plastic Injection
Contact Material	24K Gold Plated
Connector Locking Mechanism	YES
Shielding	Aluminum Foil + Braided
Conductor Gauge	26AWG Bare Copper
PACKING	
Packaging Type	Paper cable ties